


SUGGESTED TOOLS AND MATERIALS



Adjustable Wrench



Teflon Tape



Hex Wrench (supplied)



Channel Lock

BEFORE YOU BEGIN

- Turn off the main water supply
- Observe all local plumbing and building codes
- Deck hole Diameter: 1-1/4" to 1-3/8" diameter
- Maximum deck thickness is 3"
- This lavatory faucet comes completely assembled and water tested
- 15" braided stainless steel supply lines included with 9/16" compression inlets

INSTALL THE LAVATORY FAUCET

Important! Use care when installing the lavatory faucet to avoid scratching the finish.

- Unscrew NUT (7), THRUST WASHER (6) and RUBBER GASKET (5) from BODY (4)
- Feed the FAUCET SUPPLY LINES (1) through the hole in the counter top.
- Seat O-RING (2) and BASE (3) into under side of FAUCET BODY (4)
- From below, install RUBBER GASKET (5), THRUST WASHER (6) and screw on HOLD-DOWN NUT (7) Before final tightening, adjust faucet so that it is centered. Tighten HOLD-DOWN NUT to complete mounting.

WATER SUPPLY CONNECTIONS

Important! If SUPPLY LINES are too long, loop them to avoid kinking. If additional supply length is required, installer must purchase additional parts separately.

- Connect the FAUCET SUPPLY LINES (1) directly to the existing wall / floor supplies. Connect Left supply to HOT (Marked with a Red Band) and Right supply to COLD.
- Tighten the 9/16" compression nuts with small crescent wrench and do not over tighten as this may strip the threads.

TEST INSTALLED FAUCET

- Unscrew CAP BOLT (8) with AERATOR INSERT (9) and GASKET (10).
- With handle in OFF position, turn on water supplies and check all connections for leaks. Turn ON faucet for two minutes to flush water lines thoroughly. Debris in the water can damage the CERAMIC CARTRIDGE (11) causing it to leak.
- Replace CAP BOLT (8) with AERATOR INSERT (9) and GASKET (10).

SERVICE

Caution: Turn off hot and cold water supplies before beginning.

- To remove and clean or replace cartridge:
- Unscrew the SCREW (12) with the HEX WRENCH provided and pull up on HANDLE CAP (13)
- Unscrew BRASS DOME CAP (14) and pull up on CERAMIC CARTRIDGE (11)
- Inspect CARTRIDGE for debris and clean if necessary.
- Reinstall CARTRIDGE (11), DOME CAP (14) and HANDLE CAP (13)

CARE INSTRUCTIONS

To keep your new faucet looking new, please follow these simple care instructions

- DO:** Simply rinse the faucet clean with clean water and mild soap
Dry the faucet with a soft cotton cloth
- DON'T:** Do not use any abrasive cleaners, cloths or paper towels.
Do not use any cleaning agents containing acids, polish abrasives or harsh cleaner or soap

Regular and routine cleaning will reduce the need for heavy cleaning and polishing.

