


### SUGGESTED TOOLS AND MATERIALS



Adjustable Wrench



Teflon Tape



Hex Wrench (supplied)



Channel Lock

### BEFORE YOU BEGIN

- Turn off the main water supply
- Observe all local plumbing and building codes
- Deck hole Diameter: 1-1/4" to 1-3/8" diameter
- Maximum deck thickness is 3"
- This lavatory faucet comes completely assembled and water tested
- 15" braided stainless steel supply lines included with 9/16" compression inlets

### INSTALL THE LAVATORY FAUCET

**Important!** Use care when installing the lavatory faucet to avoid scratching the finish.

- Unscrew HOLD-DOWN NUT and RUBBER GASKET from BODY
- Feed the FAUCET SUPPLY LINES through the hole in the counter top.
- Seat O-RING and BASE into under side of FAUCET BODY
- From below, install RUBBER GASKET and screw on HOLD-DOWN NUT. Before final tightening, adjust faucet so that it is centered.
- Tighten HOLD-DOWN NUT to complete mounting.

### WATER SUPPLY CONNECTIONS

**Important!** If SUPPLY LINES are too long, loop them to avoid kinking. If additional supply length is required, installer must purchase additional parts separately.

- Connect the FAUCET SUPPLY LINES directly to the existing wall / floor supplies. Connect Left supply to HOT (Marked with a Red Band) and Right supply to COLD (Marked with a Blue Band)
- Tighten the 9/16" compression nuts with small crescent wrench and do not over tighten as this may strip the threads.

### TEST INSTALLED FAUCET

- With handle in OFF position, turn on water supplies and check all connections for leaks. Turn ON faucet for two minutes to flush water lines thoroughly.

### SERVICE

**Caution:** Turn off hot and cold water supplies before beginning.

To remove and clean or replace cartridge:

- Remove the CAP and SCREW with the HEX WRENCH provided and pull up on HANDLE and HANDLE BODY.
- Remove PLASTIC CAP and unscrew BRASS DOME CAP and pull up on CERAMIC CARTRIDGE
- Inspect CARTRIDGE for debris and clean if necessary.
- Reinstall CARTRIDGE, DOME CAP, PLASTIC CAP and HANDLE

### CARE INSTRUCTIONS

To keep your new faucet looking new, please follow these simple care instructions

- DO:** Simply rinse the faucet clean with clean water and mild soap  
Dry the faucet with a soft cotton cloth
- DON'T:** Do not use any abrasive cleaners, cloths or paper towels.  
Do not use any cleaning agents containing acids, polish abrasives or harsh cleaner or soap

Regular and routine cleaning will reduce the need for heavy cleaning and polishing.

